

# IP PHONE 7308SL

## NEXT GENERATION BROADBAND TELEPHONE

The InnoMedia IP Phone 7308SL offers the features you would expect on a residential or a business telephone. It features a single-line IP phone with speed dial and phone book keys, speaker phone for hands-free dialing, and function keys. It offers easy installation with menu/web/CLI based configurations, and upgradable through remote provisioning.

### KEY BENEFITS

Integrated with auto provisioning, allowing scalable commercial volume deployment.

Loaded with features for business:

- Speaker phone
- Memory buttons
- Feature functional keys
- QoS features (802.1 p/q, TOS) for optimum voice and data traffic management



*Standalone IP Phone 7308SL*

#### ■ Convenient business-phone features

The IP Phone 7308SL is equipped with features ideal for residential and business use. It is a speaker phone with convenient function keys – message, call hold, speaker, transfer and mute. Its directory button allows direct access to a contact list. The dual Ethernet ports on the IP Phone 7308SL allow users to share a WAN connection with a desktop PC.

#### ■ Comfortable voice experience

The IP Phone 7308SL effortlessly delivers the digital voice quality comparative to that of PSTN. It offers dynamic jitter buffer that accommodates network jitters adaptively. It further supports IEEE 802.1 p/q and TOS tagging to offer QoS. Even with a network of PCs connected to its LAN port, your users can be rest assured that voice quality will not be compromised, as voice packets are prioritized over data originated on the customer side, thus reducing voice packet drop and minimizing its latency.

# INNOMEDIA IP PHONE 7308SL

## ■ Plug-and-play through auto-provisioning

Compliant with many provisioning protocols, the IP Phone 7308SL can be quickly and easily auto-provisioned. It is easy for subscribers to install while reducing your operation costs by providing remote software upgrade, system provisioning and configuration capabilities. It also automatically checks for updates and downloads the latest configurations.

- A. Message
- B. Hold
- C. Transfer
- D. Mute
- E. 128 x 64 Graphics LCD
- F. Message Waiting Power/Network Status/DND/Mute
- G. Speed dial keys (M1-M10)
- H. Menu Navigation Keys
- I. OK
- J. Flash
- K. Call
- L. Cancel
- M. Re-dial
- N. Speaker phone key



## SPECIFICATIONS AND FEATURES

### Call Agent/Softswitch

- SIP 2.0
- OAM & P
- TCP/IP, UDP, DHCP, RTP, RTCP, ARP, ICMP, HTTP 1.0, SNTP, TFTP, DNS

### Codec Support

- G.711
- G.726
- G.723.1, G.729A, B, AB

### Voice Quality

- G.168 32ms Acoustic Echo Cancellation
- Voice Activity Detection
- Comfort Noise Generation

### Quality of Service

- L2 QoS IEEE 802.1p/q
- RFC2833 RTP payload for DTMF digits
- L3 QoS DiffServ or Precedence

### Network Interface

- Dual 10/100 Base-T Uplink/Downlink ports

### Audio Interface

- Handset
  - Adjustable Volume Control
- Speakerphone
  - Adjustable Volume Control

### Power Requirement

- External power adapter  
Input 100-230V AC,  
Output 9VDC, 400mA or 1000mA

### Regulatory Approvals

- UL 1950, C/uL
- CE
- FCC Part 15 Class B
- CISPR 22 Class B

### Physical

- Dimension: 2.5x7x9 in (HxWxD)
- Weight: 1lb, 12 oz

### Display

- 128x64 Graphics LCD
- Visual Message Waiting Indicator (VMWI)
- Power
- Network State
- Mute/DND

### Call Features

- Call Waiting
- Call Hold
- Blind Transfer
- Attend Transfer
- Forward when busy
- Forward when no answer
- Forward Unconditionally
- Hotline

### Menu System

- Call Log Access
- 100-number Phonebook
- 10 entries each for missed/answered /dialed calls

### Package Includes

- Ethernet Cable
- AC Adapter

### Operating Environment

- Temperature: 32-104°F (0-40°C)
- Humidity: 20%-90%, non-condensing

# INNOMEDIA IP PHONE 7308SL

## MODEL VARIATIONS

	Number of Lines	PoE	LCD Size/ Resolution	3 Way Conference	HeadSet Jack	Business Buttons	WideBand Codec	Full Duplex Speaker
7308SL*	1		3-inch 128x64			■		
6308SL1	1	■	3-inch 128x64	■		■	■	■
6308SL2	2	■	3-inch 128x64	■		■	■	■
6308M4	4	■	3.5-inch 320x240	■	■	■	■	■
6308M6	6	■	4-inch 480x272	■	■	■	■	■

\* 7308SL does not support DMS

## WWW.INNOMEDIA.COM

### InnoMedia Pte Ltd.

10 Science Park Road #03-04  
The Alpha, Singapore Science Park II, SINGAPORE 117684  
Tel: (65) 6872 0828; Fax: (65) 6872 0900

### InnoMedia Technology Inc.

3F, No. 3, Industrial East Road IX  
Hsinchu Science-Based Industrial Park, Hsinchu TAIWAN 300  
Tel: (886) 3 564 1299; Fax: (886) 3 564 1589

### InnoMedia, Inc.

128 Baytech Drive  
San Jose, CA 95134 USA  
Tel: (408) 432-5400; Fax: (408) 432-5404

### InnoMedia Inc. Beijing Rep. Office

Room 1328, JingXin Building,  
Jia 2# North Road Dong San Huan,  
Chao Yang District  
Beijing, 100027  
P. R. China  
Phone: (86) 10-65261186, (86) 10-65261189  
Fax: (86) 10-65261186, (86) 10-65261189 ext 210

© 2008-2009 InnoMedia Inc. All rights reserved. InnoMedia and the InnoMedia logo are trademarks of InnoMedia Inc. PacketCable is a trademark of Cable Television Laboratories, Inc. All other brand and product names may be trademarks of their respective companies. Specifications subject to change without notice.

v1.5-D 05/09

